



 PRODUCT-DETAILS

CP435T

CP430 BP-ETH Control Panel 5.7" STN Touc



General Information

Extended Product Type	CP435T
Product ID	1SBP260193R1001
ABB Type Designation	CP435T
EAN	3471522601933
Catalog Description	CP430 BP-ETH Control Panel 5.7" STN Touc
Long Description	CP435 T Control Panel 1 menu 6 defined keys 7" TFT Touch screen 64K Colors

Additional Information

ABB Type Designation	CP435T
Ambient Air Temperature	Operation 0 ... +50 °C Storage -10 ... +60 °C
Battery Type	Portable
CN8	85371091
Communication	Depend on Driver
Communication Interface	no
Communication Speed	4.8 ... 187.5 kBd

Country of Origin	Taiwan (Chinese Taipei) Germany
Customs Tariff Number	85371091
Data Sheet, Technical Information	1SBC159107L0202
Declaration of Conformity - CE	1SBD240516C1000
Display Type	TFT Touch + keys
EAN	3471522601933
Fieldbus Interface Type	Modbus RTUAC500_ModbusASCIlothers (contact us)
Frame Size	Undefined
Fuse Size	5 x 20_MMTx
Fuse Type	SLEEK.36ESr
Gross Weight	1.31 kg
Instructions and Manuals	1SBC159108M0201
Instructions and Manuals (Part 2)	1SBC159106M0202
Invoice Description	CP430 BP-ETH Control Panel 5.7" STN Touc
Made To Order	No
Memory Size User Data	512 kB
Memory Size User Program	8000 kB
Memory Type User Data	512 kilobyte RAM
Memory Type User Program	8 MB ROM
Minimum Order Quantity	1 piece
Mounting Position	0 to 135 °
Mounting Type	Front face
Mounting on DIN Rail	No
Number of Characters Per Line	100
Number of Display Lines	60
Number of Function Keys	6
Number of LEDs	0
Operating Mode	off-lineon-line
Order Multiple	1 piece
Power Supply	20 V·A 24 V DC
Product Main Type	CP435
Product Name	Control Panel
Product Net Depth / Length	47 mm
Product Net Height	176 mm
Product Net Weight	0.86 kg
Product Net Width	231 mm
Product Type	PLC-CP400
Profibus	No
Programming Software	CP400 Soft
Quote Only	No
Real-time Clock	Yes
Release Type	V11.13.10
RoHS Information	1SBD340002R0202
Screen Color	64k colors
Screen Resolution	800 x 480 pixel

Screen Size	16:9 wide screen 7 in
Screen Type	TFT color, CCFL backlight, touch screen
Security	password protection with 9 user levels
Selling Unit of Measure	piece
Serial Port 1 Type	RS232/RS485
Serial Port 2 Type	RS232/RS422/RS485
Service Life	50000 hour
Short Description	CP435 T Control Panel 7" TFT Touch screen 64KCol
Short-Circuit Protective Devices	gG Type Fuses Integrated
Software Function	alarm managementrecipe managementtrendsmacro & laddersub-screen
Stocked At (Warehouses)	Menden, Germany Bairro Santo Antonio, Brazil
Supply Voltage	20.4 ... 27.6 V DC
UL Certificate	NRAQ.E240320
UNSPSC	32151703
USB Port 1 Type	2 Host Ver. 2.0
USB Port 2 Type	1 Device Ver. 2.0
Viewing Area Height	92.4 mm
Viewing Area Length	153.7 mm
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
cUL Certificate	1SAA960000-1709
eClass	27-33-02-01

Categories

PLC Automation → Legacy Products → CP400 → Devices

