




---

 PRODUCT-DETAILS

## PSTB370-690-70

### PSTB370-690-70 Softstarter - 370 A - Main Circuit 400 ... 690 V AC




---

**General Information**

Extended Product Type	PSTB370-690-70
Product ID	1SFA895015R7000
EAN	7320500255827
Catalog Description	PSTB370-690-70 Softstarter - 370 A - Main Circuit 400 ... 690 V AC
Long Description	Softstarter PSTB370-690-70 for max 690V main voltage and 110 - 240V 50/60Hz control supply voltage

---

**Ordering**

Minimum Order Quantity	1 piece
Customs Tariff Number	8503009999

---

**Popular Downloads**

Data Sheet, Technical Information	1SFC132005C0201
Instructions and Manuals	1SFC132003M0201

## Dimensions

Product Net Width	366 mm
Product Net Height	460 mm
Product Net Depth / Length	361 mm
Product Net Weight	31 kg

## Technical

Rated Operational Voltage	Main Circuit 400 ... 690 V AC
Rated Control Supply Voltage (U <sub>s</sub> )	100 ... 250 V AC
Rated Control Circuit Voltage (U <sub>c</sub> )	DC Operation 24 V
Rated Frequency (f)	50/60 Hz Main Circuit 50 / 60 Hz
Rated Operational Power - In-Line Connection (Pe)	(400 V) 200 kW (500 V) 257 kW (690 V) 355 kW
Rated Operational Current - In-Line Connection (I <sub>e</sub> )	370 A
Rated Operational Power - Inside Delta Connection	at 400 V 355 kW at 500 V 450 kW at 690 V 600 kW
Rated Operational Current - Inside Delta Connection	640 A
Service Factor Percentage	115 %
Overload Protection	Build-in electronic overload protection
Integrated Electronic Overload	Yes
Starting Capacity at Maximum Rated Current I <sub>e</sub>	3xI <sub>e</sub> for 15s
Ramp Time	0 ... 120 second [unit of time] 1 ... 120 second [unit of time]
Initial Voltage During Start	30 ... 70 %
Step Down Voltage Special Ramp	100 ... 30 %
Current Limit Function	1.5 ... 7xI <sub>e</sub>
Switch for Inside Delta Connection	Yes
Run Signal Relay	Yes
By-pass Signal Relay	Yes
Fault Signal Relay	Yes
Overload Signal Relay	Yes
Analog Outputs	0...10 volts 0...20 mA 4...20 mA
Signal Indication Ready to Start/Standby ON (LED)	Green
Signal Indication Protection (LED)	Yellow

Signal Indication Fault (LED)	Red
Number of Starts Per Hour at 3.5*Ie for 7 sec. 50% ON Time 50% OFF Time	10
Communication	FiledBusPlug(Standard)
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Main Circuit: Bars
Connecting Capacity Main Circuit	Hole Diameter 10.5 mm Width and Thickness 25x6 mm
Connecting Capacity Control Circuit	Rigid 1 x 2.5 mm <sup>2</sup> Rigid 2 x 1.5 mm <sup>2</sup>
Connecting Capacity Supply Circuit	Rigid 1 x 2.5 mm <sup>2</sup>
Tightening Torque	Control Circuit 0.5 N-m Main Circuit 35 N-m Supply Circuit 0.5 N-m
Product Main Type	PSTB370

## Environmental

Ambient Air Temperature	Operation 0 ... +50 °C Storage -25 ... +70 °C
-------------------------	--

## Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
RoHS Information	1SFC132035D0201
RoHS Status	No declaration needed
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Certificates and Declarations

Declaration of Conformity - CE	1SFA1-76
--------------------------------	----------

## Container Information

Package Level 1 Width	440 mm
Package Level 1 Depth / Length	550 mm
Package Level 1 Height	440 mm
Package Level 1 Gross Weight	40 kg
Package Level 1 EAN	7320500255827
Package Level 1 Units	1 piece

## External Classifications and Standards

Object Classification Code	Q
----------------------------	---

ETIM 7	EC000640 - Soft starter
ETIM 8	EC000640 - Soft starter
ETIM 9	EC000640 - Soft starter
eClass	V11.0 : 27370907
UNSPSC	39121521

---

## Categories

---

Drives → Softstarters → Softstarters → PST(B) Softstarters → PST105

Low Voltage Products and Systems → Control Products → Softstarters → Softstarters → PST(B) Softstarters → PST105

