



Figure similar

Spare part SIMATIC S7, Digital input SM 326, 8 DI; 24 V DC, NAMUR, fail-safe NAMUR input for SIMATIC S7F systems, up to Category 4 (EN 954-1)/ SIL3 (IEC61508)/PLE (ISO13849), 1x 40-pole

Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	160 mA
from backplane bus 5 V DC, max.	90 mA
Encoder supply	
Number of outputs	8
Type of output voltage	8.2 V DC
Power loss	
Power loss, typ.	4.5 W
Digital inputs	
Number of digital inputs	8; 8 (one-channel); 4 (two-channel)
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	8; vertical setup
— up to 60 °C, max.	8; horizontal set up
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	in accordance with DIN 19234 or NAMUR
Input current	
• for signal "0", max. (permissible quiescent current)	0.35 to 1.2 mA
• for signal "1", typ.	2.1 to 7 mA
Input delay (for rated value of input voltage)	
for NAMUR inputs	
— at "0" to "1", max.	1.2 to 3 ms
— at "1" to "0", max.	1.2 to 3 ms
Cable length	
• shielded, max.	200 m
• unshielded, max.	100 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Fail-safe operation	Yes
• Group error SF (red)	Yes
Ex(I) characteristics	

Module for Ex(i) protection	Yes
maximum values for connecting terminals for gas group IIC	
• Uo (no-load voltage), max.	10 V
• Io (short-circuit current), max.	13.9 mA
• Po (power output), max.	33.1 mW
• Co (permissible external capacity), max.	3 µF
• Lo (permissible external inductivity), max.	80 mH
• Um (voltage at non-intrinsically safe connecting terminals), max.	60 V DC/30 V AC

Potential separation	
Potential separation digital inputs	
• between the channels	Yes
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes

Isolation	
Isolation tested with	500 V DC

Standards, approvals, certificates	
Highest safety class achievable in safety mode	
• acc. to DIN VDE 0801	AK 4 (one channel), AK 5 und 6 (two channel)
• acc. to EN 954	4
• Performance level according to ISO 13849-1	e
• SIL acc. to IEC 61508	SIL 2 (single-channel), SIL 3 (two-channel)

Use in hazardous areas	
• ATEX certificate	99 ATEX 2671 X

Ambient conditions	
Ambient temperature during operation	
• max.	60 °C

connection method	
required front connector	40-pin

Dimensions	
Width	80 mm
Height	125 mm
Depth	120 mm

Weights	
Weight, approx.	482 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-04
	eClass	12	27-24-22-04
	eClass	9.1	27-24-22-04
	eClass	9	27-24-22-04
	eClass	8	27-24-22-04
	eClass	7.1	27-24-22-04
	eClass	6	27-24-22-04
	ETIM	9	EC001419
	ETIM	8	EC001419
	ETIM	7	EC001419
	IDEA	4	3566
	UNSPSC	15	32-15-17-05

Approvals / Certificates			
General Product Approval	For use in hazardous locations	Functional Safety	Marine / Shipping



Miscellaneous



Type Examination Certificate





[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

last modified:

3/3/2025